

Make	mitsubishi
Model	Shogun/Pajero/Montero Turbo Diesel 2.8
Engine	DT
Year	1994-99

Application	Recommendation	Capacity (ltr)
Engine (DT)	Recommended EURODIESEL (bb)	6.5 / 7.8 (c)
	Alternative DIESEL (bb)	
Manual Transmission	SX 75W90 GL-4 (t)	3.7
Automatic Transmission	AQM® (y)	8.5
Differential	EP 80W90 GL-5	3.2
Coolant (30%)	XSTREAM GREEN (p)	8 - 10.5
Front Differential	EP 80W90 GL-5	1.2
Transfer Box	SX 75W90 GL-4	2.5 / 2.9
Brake & Clutch Fluid	DOT 3	
Wheel Bearings	MULTIPURPOSE LITHIUM GREASE No.2	
Power Steering	PSF	
Hide Notes Hide Oil Change Intervals		

Lubricant / Capacity Notes

- bb. Alternative recommendations, Engine (Diesel): -20°C to 40°C, 10W-30; >-15°C, 15W-40; >-10°C, 20W-40; 0°C to 40°C, 30; <10°C, 5W-30
- c. Without/With oil cooler
- t. Alternative recommendations: 75W-85W; 75W-90
- y. Alternative recommendations, >1996: Refer to Owners Handbook
- p. Preferred grade: Refer to Owners Handbook

General Notes

There are no notes to display for this model

Oil Change Intervals

Engine

Miles Max	4500
Km Max	7500
Months Max	6

Comma Product recommendations are based upon the technical data provided by the vehicle manufacturer. For a more detailed description of the correct lubricant for your vehicle please refer to the handbook or manual. Note: MY 2001=Model Year 2001

© copyright

OATS T's and C's