Make	MITSUBISHI
Model	Shogun/Pajero/Montero 3.0 24V V6
Engine	Р
Year	1994-99

Application	Recommendation	Capacity (ltr)		
Engine (P)	Recommended XT2000 (s)	4.6		
	Alternative SUPER (s)			
Manual Transmission	SX 75W90 GL-4 (t)	2.5		
Automatic Transmission	AQM® (y)	7.5		
Differential	EP 80W90 GL-5	2.6		
Coolant (30%)	XSTREAM GREEN (p)	9.5 / 10.5		
Brake & Clutch Fluid	DOT 3			
Wheel Bearings	MULTIPURPOSE LITHIUM GREASE No.2			
Front Differential	EP 80W90 GL-5	1.2		
Power Steering	PSF			
Transfer Box	SX 75W90 GL-4	2.3 / 2.9		
Hide Notes Hide Oil Change Intervals				

## Lubricant / Capacity Notes

s. Alternative recommendations, Engine (Petrol): -30°C to 40°C, 10W-30; >-30°C, 10W-40; >-30°C, 10W-50; >-15°C, 15W-40; >-15°C, 15W-50; >-10°C, 20W-40; >-10°C, 20W-50; <-10°C, 5W-20; <10°C, 5W-30; <20°C, 5W-40; <20°C, 5W-50

t. Alternative recommendations: 75W-85W; 75W-90

y. Alternative recommendations, >1996: Refer to Owners Handbook

p. Preferred grade: Refer to Owners Handbook

## **General Notes**

There are no notes to display for this model

## **Oil Change Intervals**

Engine

Miles Max	9000
Km Max	15000
Months Max	12

Comma Product recommendations are based upon the technical data provided by the vehicle manufacturer. For a more detailed description of the correct lubricant for your vehicle please refer to the handbook or manual. Note: MY 2001=Model Year 2001

© copyright

OATS T's and C's