

Make	mitsubishi
Model	Shogun/Pajero/Montero 3.5 V6
Engine	P
Year	1994-99

Application	Recommendation	Capacity (ltr)
Engine (P)	Recommended XT2000 (s)	5
	Alternative SUPER (s)	
Manual Transmission	SX 75W90 GL-4 (t)	3.7
Automatic Transmission	AQM® (y)	8.5
Differential	EP 80W90 GL-5	3.2
Coolant (30%)	XSTREAM GREEN (p)	8 - 10.5
Wheel Bearings	MULTIPURPOSE LITHIUM GREASE No.2	
Power Steering	PSF	
Transfer Box	SX 75W90 GL-4	2.5 / 2.9
Brake & Clutch Fluid	DOT 3	
Front Differential	EP 80W90 GL-5	1.2
Hide Notes Hide Oil Change Intervals		

Lubricant / Capacity Notes

- s. Alternative recommendations, Engine (Petrol): -30°C to 40°C, 10W-30; >-30°C, 10W-40; >-30°C, 10W-50; >-15°C, 15W-40; >-15°C, 15W-50; >-10°C, 20W-40; >-10°C, 20W-50; <-10°C, 5W-20; <10°C, 5W-30; <20°C, 5W-40; <20°C, 5W-50
- t. Alternative recommendations: 75W-85W; 75W-90
- y. Alternative recommendations, >1996: Refer to Owners Handbook
- p. Preferred grade: Refer to Owners Handbook

General Notes

There are no notes to display for this model

Oil Change Intervals

Engine

Miles Max	9000
Km Max	15000
Months Max	12

Comma Product recommendations are based upon the technical data provided by the vehicle manufacturer. For a more detailed description of the correct lubricant for your vehicle please refer to the handbook or manual. Note: MY 2001=Model Year 2001

© copyright

OATS T's and C's