

Make	SUZUKI
Model	Vitara 1.6 4WD (3dr) (SE 416)
Engine	P
Year	1988-94

Application	Recommendation	Capacity (ltr)
Engine (P)	Recommended EUROLITE (e)	4.5
	Alternative LITE (e)	
Manual Transmission	SX 75W90 GL-4	1.5
Automatic Transmission	AQM®	5.1
Differential	SX 75W90 GL-5	2.2
Coolant (50%)	XSTREAM GREEN	5.5
Limited Slip Differential (where fitted)	LS 80W90 GL-5	
Transfer Box	SX 75W90 GL-4	1.7
Front Differential	SX 75W90 GL-5	1
Power Steering	PSF	
Brake Fluid	DOT 3	
Wheel Bearings	MULTIPURPOSE LITHIUM GREASE No.2	
Hide Notes Hide Oil Change Intervals		

Lubricant / Capacity Notes

e. Alternative recommendations, Engine (Petrol): 10W-30; >-7°C, 20W-40 / 20W-50

General Notes

There are no notes to display for this model

Oil Change Intervals

Engine

Miles Max	6000
Km Max	10000
Months Max	6

Comma Product recommendations are based upon the technical data provided by the vehicle manufacturer. For a more detailed description of the correct lubricant for your vehicle please refer to the handbook or manual. Note: MY 2001=Model Year 2001

© copvright

OATS T's and C's